

CLASS 1 BUILDING PRODUCT INFORMATION SHEET



PRODUCT NAME

COREtec hardfloor range

PRODUCT DESCRIPTION AND ITS INTENDED USE

As the original 100% waterproof core flooring with its wide selection of authentic natural looks. With COREtec, get a floor you love – and a floor that lasts.

Our 100% waterproof, kidproof, petproof flooring stands up to real life and then some. So naturally, all COREtec floors come with a limited lifetime residential warranty. COREtec flooring is easy to install, easy to care for and easy to live with. COREtec flooring is thicker, more comfortable and quieter underfoot while providing excellent durability. All with a lifetime residential warranty.

KEY TECHNICAL SPECIFICATIONS

AUTHENTICS

- Usage: Residential & Commercial
- Width: 180mm
- Length: 1830mm
- Thickness: 8mm
- Wear Layer: 0.55mm
- Box: 8 planks per box (2.65 m2)
- Box weight: 23 kgs
- Product identifier: 50LVRE

NATURALS

- Usage: Residential & Commercial
- Width: 182mm
- Length: 1220mm
- Thickness: 8mm
- Wear Layer: 0.55mm
- Box: 12 planks per box (2.66 m2)
- Box weight: 22.04 kgs
- Product identifier: UV426/427

NATURALS XL

- Usage: Residential & Commercial
- Width: 228mm
- Length: 1830mm
- Thickness: 8mm
- Wear Layer: 0.55mm
- Box: 6 planks per box (2.504 m2)
- Box weight: 22 kgs
- Product identifier: UV376/124

NATURALS HERRINGBONE

- Usage: Residential & Commercial
- Width: 109mm
- Length: 659mm
- Thickness: 8mm
- Wear Layer: 0.55mm
- Box: 32 planks per box (2.324m2)
- Box weight: 20 kgs
- Product identifier: UV579

STONE

- Usage: Residential & Commercial
- Width: 457mm
- Length: 915mm
- Thickness: 8mm
- Wear Layer: 0.55mm
- Box: 5 planks per box (2.09 m2)
- Box weight: 23.6 kgs
- Product identifier: 50CERAE (Eifel), 50CERAK (Katla), 50CERAT (Teneguia)

BABY THRESHOLD

- Usage: Residential & Commercial
- Width: 35mm
- Length: 240mm
- Thickness: 10mm
- Product identifier: 70BT3

BABY THRESHOLD WITH TRACK

- Usage: Residential & Commercial
- Width: 32mm
- Length: 240mm
- Thickness: 12mm
- Product identifier: BT7IH

FLUSH STAIR NOSE

- Usage: Residential & Commercial
- Width: 52.6mm
- Length: 240mm
- Thickness: 19mm
- Product identifier: 70STF3

STAIR CAP

- Usage: Residential & Commercial
- Width: 52.6mm
- Length: 240mm
- Thickness: 29.46mm
- Product identifier: 70ST3

T-MOLD

- Usage: Residential & Commercial
- Width: 32mm
- Length: 240mm
- Thickness: 12mm
- Product identifier: 70TM3

T-MOLD WITH TRACK

- Usage: Residential & Commercial
- Width: 32mm
- Length: 240mm
- Thickness: 12mm
- Product identifier: TM7IH

CLASS 1 BUILDING PRODUCT INFORMATION SHEET

COREtec
FLOORS

LEGAL AND TRADING NAME OF THE MANUFACTURER

US Floors International Inc

Address for service:
27 Souverainestraat
Kruisem, 9770
Belgium

Website: www.coretecfloors.com
Email: info@usfloors.be

LEGAL AND TRADING NAME OF THE IMPORTER

The Interiors Group NZ

Address for service:
PO Box 105 806
Auckland, 1010

Website: www.theinteriorsgroup.nz
Email: support@theinteriorsgroup.nz
Phone: (09) 304 0578
NZBN: 5741329

RELEVANT BUILDING CODE CLAUSES

- B2 Durability: Performance clauses B2.3.1(a) (ii) and (iii) and B2.3.2
- C3 Fire affecting areas beyond the fire source clause C3.4(b)
- D1 Slip
- E3 Internal moisture
- F2 Hazardous Building Materials: Performance clause F2.3.1
- G6 Airborne & Impact Sound clauses /AS1

STATEMENT ON HOW THE BUILDING PRODUCT IS EXPECTED TO CONTRIBUTE TO COMPLIANCE

- **B2.3.1(c) (i) and (ii) and B2.3.2:** COREtec flooring is designed and manufactured to be durable, meeting Class 23 / 33 (EN ISO 10874) when the flooring is installed by a professional installer, furthermore maintained to the standard required in the care and maintenance guide. Refer to the care guide for further information. Care guides and warranties available online at www.carpetcourt.nz/warranties
- **C3.4(b):** COREtec flooring meets or exceeds the performance criteria required by clause C3.4(b) passing the required Critical radiant Flux testing with Bfl - S1 (EN 13501).
- **D1.2.1.2(b) and 2.1.5:** COREtec flooring is deemed acceptable wet slip as per table 2, 2.1.2(b), where internal access routes shall be assumed to be dry in normal use.
- **E3.3.3, E3.3.5, E3.3.6:** COREtec is easily cleaned and impervious per NZWTA testing to ISO4670 (modified) when installed and maintained in accordance with COREtec's laying instructions.
- **F2.3.1:** COREtec flooring is manufactured in facilities that meet Green Guard Gold standards. The GREENGUARD Gold Certified standard goes beyond the regular certification to include criteria for even more chemicals and requires lower total VOC emissions levels to ensure that products are acceptable for use in environments like schools, nurseries, and healthcare facilities.
- **G6:** As1 COREtec flooring exceeds the IIC (Impact Insulation Class) of 55.

LIMITATIONS ON THE USE OF THE BUILDING PRODUCT

- Damage due to adhesives or tape, scratches, gouges, scuffs, punctures, cuts, indentations, burns, accidents, lack of proper furniture rests or any intentional misuse of the product.
- Loss of finish gloss over time is consistent with normal wear & tear and is not a product flaw.
- It is normal and expected for there to be colour variations due to use of natural components, exposure to UV light and/or sunlight, and age of material. Therefore, colour inconsistency between samples, replacement product or illustrations and actual product is not a manufacturing flaw.
- Manufacturer makes no guarantee that COREtec flooring products will match or coordinate with customer furnishings, trim, cabinetry, railings, etc.
- Noncompliance with installation instructions and maintenance guidelines as recommended by COREtec flooring will void the warranty.
- Manufacturer cannot assume responsibility for the suitability of flooring material and accompanying products for each individual installation as manufacturer has no control over the installer's proper application. Should an individual piece be doubtful as to appearance or dimension the installer should not use this piece.
- Cracking, warping, soiling, fading, improper maintenance or abuse caused by items such as roller skates, golf shoes or pets.
- Floor covering installed in inappropriate locations is excluded from this warranty.
- The flooring must be used only indoors in a dry, climate-controlled area.
- The floor must be installed properly and according to COREtec installation instructions.
- Must be installed by a professional installer.
- The flooring must be maintained in accordance with COREtec maintenance instructions.

CLASS 1 BUILDING PRODUCT INFORMATION SHEET

COREtec
FLOORS

- Colour change can also occur as the result of ozone, emissions from heating fuels and air conditioners, pesticides, cleaning agents, benzol peroxide and other household items.
- Gloss reduction or surface scratches are not considered surface wear. Dull finish can be corrected with spot or overall recoating care systems.
- Care guides and warranty is available online at www.carpetcourt.nz/warranties.

DESIGN REQUIREMENTS THAT WOULD SUPPORT THE APPROPRIATE USE OF THE BUILDING PRODUCT

- Sheers and curtains offer protection and are recommended to protect your purchase, especially in North and West facing areas of your home.
- Floor must be flat, solid and level.
- COREtec floors are made to perform in owner occupied, single family, residential homes, or for the original purchaser in commercial areas like Retail: novelty shops/boutiques, product display areas, sales floors, showrooms, hair salons, hallways, entryways (walk off mats required); (1) Medical Offices: waiting rooms, patient rooms, examination rooms, storage rooms, hallways, entryways (walk off mats required); (2) Hotels: guest rooms, conference/meeting rooms, lobby; (3) Offices and Restaurants: offices, conference/meeting rooms, showrooms, restaurant floor, break rooms; (4) Institutional: classrooms, training rooms, meeting rooms, commons areas, residence halls, hallways
- COREtec flooring is made for indoor use only.

INSTALLATION REQUIREMENTS

- Must be installed by a professional installer.
- The floor must be installed properly and according to manufacturer instructions and AS/NZS 1884-2013.

MAINTENANCE REQUIREMENTS

- Preventative maintenance - Always protect floors when moving heavy objects to prevent permanent scratches and tears. Use appropriate wide floor protectors under tables, chairs, and any other heavy home furnishing to avoid permanent damage. Walk-off mats should be used at all entrances to absorb soil and moisture. If mats are placed directly on top of the resilient floors, use mats without latex or rubber backings to avoid possible discoloration. Use appropriate window coverings to avoid direct sunlight as this can fade or change the colour of the flooring. Furniture with castor wheels should be easy swivelling, large surface, non-staining and suitable for resilient floors. Do not use ball-type castors as these can damage the floor. Protective mats are required under office chairs.
- Routine maintenance - Daily removal of dirt and dust is important to prevent particles from abrading the surface of resilient floors. Sweeping, dust mopping, and vacuuming are recommendations to remove soil particles that can result in scratches and worn appearances. Do not use vacuums with rotating beater bars. Periodic wet cleaning will be necessary to help maintain the floor's appearance. Always pre-vacuum or dust mop before any type of wet cleaning. Appropriate vinyl floor cleaning equipment and cleaning agents (neutral pH floor cleaners) are recommended. Do not use abrasive cleaners or cleaning agents that leave dull residues on the surface of the floors. Follow the cleaning manufacturer's instructions for damp mopping and application. If rinsing is necessary, use clean water and expedite drying with air movers or fans. Neutral pH floor cleaner is recommended for general spotting and cleaning. Never use floor polish or floor cleaning wax, oil soaps, etc. These products can damage and/or leave a film on the flooring. Do not buff, wax or use cleaning products that contain surfactants. Never steam clean or use a steam mop on the floor.
- Spot & Spill removal - Our flooring products are engineered to resist and minimise common staining. Absorb wet spills as quickly as possible by blotting with paper or cloth towels. Rinse with water if necessary and blot dry. Dried spots should be removed by gentle agitation and rinsed with water. Blot dry. Use neutral pH floor cleaners formulated for vinyl floor cleaning. Do not use detergents or abrasive cleaners since these products can leave a dull residue. Use rubbing alcohol (isopropyl alcohol) with a clean white cloth for spots requiring a solvent type cleaner that water and cleaning agents cannot remove. Please note that some stain conditions may become permanent. Safety Caution: The surfaces of resilient floors change during wet cleaning and finish applications. Use appropriate safety measures.
- Care guides and warranties available online at www.carpetcourt.nz/warranties.

For supporting information please contact help.product@theinteriorsgroup.nz

IS THE BUILDING PRODUCT/BUILDING PRODUCT LINE SUBJECT TO WARNING OR BAN UNDER SECTION 26 OF THE BUILDING ACT 2004?

No

Version: 001
Date: December 2023